





Art No. PA0027

Mini USB Car Charger

Suit for car Electronic Product which input 5V DC to supply power continuously and steadily.

Feature:

- This adapter plugs into your car's cigarette jack to become a powered USB port
- Use your car to charge any devices (digital cameras, PDAs, mobile phones, USB accessories and more) that can rely on USB for power!
- Charge your mobile phone from any standard cigarette lighter in any vehicle. (Use together with USB charging cable.)
- Fit all electronic appliances that use a USB charging cable
- With LED indicator and fuse safety protection
- With easy pulling hook to plug

Specification:

Input Voltage:	12~24V DC	
Input Current:	When input 12V DC, 0.55A	
	When input 24V DC, 0.30A	
Output Voltage:	$5.1V \pm 0.5V$ DC (empty)	
Output Current:	1200mA	
Output short Voltage:	0~0.2VDC	
Output Voltage Accuracy:	±5%	
Output Noise:	≤100mV	
Output Efficiency:	≥80%	
Output Normal Rated Power:	6W	
Dimension:	45 x 32mm	
Weight:	15g	



























Art No. PA0027

Mini USB Car Charger

Environment:

- Operating temperature range: -40°C~+65°C, Humidity: 10%~85%
- Storage temperature range: -40°C~+85°C, Humidity: 10%~85%

Test Parameters:

No.	Test item	Test method	Criteria
1	USB Plug	Insert and pull-out the Plug from socket	Insert force: 0.8~3.0Kg
	pulling	to test their acting power	Pull force: 0.8~3.0Kg
	force Test		
2	Spring leaf	Insert and pull-out the Plug from socket	Insert force: 1.5~3.5Kg
	test	to test their acting power	Pull force: 1.5~3.5 Kg
3	Vibration	5~10Hz, amplitude as 3.5mm per	Spring leaf, shell and
	test	minute and 9~200Hz, acceleration	Function didn't change
		10m/s 2,3 axial direction, to sweep	
		vibration 5 times each direction (3*50	
		minutes), Power supply didn't damaged	
4	Heat-proof	Test after keeping 96 hours in the	1. Output voltage change:
	test	environment of 60°C and 30 minutes in	5.1±5%VDC
		roomt emperature	2. Contact Resistance of
			each joint: 1Ω & below
5	Average	In the environment of 25°C, to test	The average lifetime:
	operation	operation life continuously	10,000 hours
	life test		
6		Output short-circuit protection test , and	Auto stop working
	protection	connect positive and negative poles	




























Art No. PA0027

Mini USB Car Charger


Product characteristic:

• USB Port 5.1V ± 5% 2.7V ± 5% GND 2.0V ± 5%

• Output voltage graph:



• Product dimension view (Unit: mm):



Packaging Information:

• Packing Dimension: 80x200x40mm

Packing Weight: 0.04kg

• Carton Dimension: 520x360x370 mm

Carton Q'ty: 160pcsCarton Weight: 6.7kgs

















