Best Connectivity

LogiLink®
www.LogiLink.com

Art No. PC0002

PCI Express Card,
1-Port eSATA + 1-Port Internal SATA + 1-Port ATA133

Specification:
General
- Chipset: Jmicron JMB363
- 1 External eSATA port + 1 Internal SATA port + 1-Port ATA133
- Compliant with PCI-Express Revision 1.0a
- Single-Lane (x1) PCI-Express with throughput up to 2.5Gbps
- Plug & Play compatible
- Supports windows 2000/2003/NT/XP/Vista/7

RAID Controller
- Supports up to 0, 1, JBOD RAID function

Serial ATA Interface
- Compliant with Serial ATA II Specification Revision 1.0
- Compliant with Gen1m, Gen2m (External SATA connection, eSATA)
- Supports internal PHY with each PHY supporting up to two SATA devices
- Data transfer rate up to 3.0Gbps
- Backward Compatible to SATA 1.0 Specification
- Supports Native Command Queue (NCQ) on SATA II port

- Supports Port Multiplier with Command-based Switching on SATA II port

Ultra ATA-133 / IDE interface
- Compliant with Bus Master Programming interface for IDE ATA Controller Revision 1.0
- Supports up to UDMA6 transfer mode of PATA

Package Contents:
- 1 x PCI Express Card for 1 x eSATA + 1 x SATA + 1x ATA133
- 1 x SATA Cable
- 1 x CD Driver

Packaging Information:
- Packing Dimension: 170x183x61 mm
- Packing Weight: 0.17kg
- Carton Dimension: 400x400x370 mm
- Carton Q'ty: 40pcs
- Carton Weight: 7kgs

PC0002

4 260113 560709

Made in China

RoHS compliant CE