

Art No. UA0141

USB2.0 4-Port Hub

The UA0141 is very well shielded owing to its metallic casing and as such is the optimum solution for an industrial use. It can be mounted below the table or at the wall. This creates order at the work place. The power pack contained in the scope of supply provides for extra power with current hungry USB devices. Also, diagnostic LEDs provide port status for each port and power status.

Features:

- Compliant to USB1.1/2.0 Specification
- Supports USB2.0 High-Speed up to 480Mbps

LogiLink.

- 1 x up-stream port and 4 x down-stream LED status indicator ports support
- Equipped with over-current Detection & Protection
- Connects up to 127 USB devices

Technical Specifications:

- With external power adapter (5V, 2A)
- Stable and robust metal housing
- Ideal for wall mounting
- Plug & Play
- Supports Windows 98SE/ME/2000/ XP/2003/Vista/7, and Mac OS 8.6 or above

Technical Specifications.		
Dimensions ($W \times H \times D$)	117x20×45 mm	
Weight	130g	
Power Adapter	100-240V AC, 50-60Hz, 2000mA	
Input Voltage	Without Power Adapter	5V DC, 500 mA
	With Power Adapter	5V DC, 2000 mA
Cable Length	1 m	
Operating Temperature	-5°C to 45°C	
Storage Temperature	-10°C to 60°C	

Package Content:

Packaging Information:

- 1 x 4-Port USB HUB Packing Dimension: 168x117x60 mm
- 1 x USB Cable • 1 x Power Adapter
- Packing Weight: 0.34kg
- Carton Dimension: 380x300x300 mm
- 1 x User Manual
- Carton Q'ty: 25pcs
- Carton Weight: 9kgs







